

Supplemental Specification
901-S-404-1
Recycled Hot Bituminous Pavement

**OFFICE OF STATE AID ROAD CONSTRUCTION
MISSISSIPPI DEPARTMENT OF TRANSPORTATION**

DATE: April 14, 1994

SUBJECT: RECYCLED HOT BITUMINOUS PAVEMENT

Section S-404; Recycled Hot Bituminous Pavement, of the 1989 Edition of the Standard Specifications for State Aid Road and Bridge Construction, is hereby amended as follows:

901-S-404.01--Description: Under Subsection S-404.01 delete the last sentence of the first paragraph on page 4-38 also delete the second paragraph on page 4-38.

901-S-404.02--Specific Requirements: Under Subsection S-404.02 on line three (3) of the first paragraph, page 4-38 delete-(except surface).

Delete the second (2) paragraph, of Subsection S-404.02, page 4-38 and substitute the following:

Reclaimed bituminous pavement materials, not to exceed 30 percent of the total mix by weight, may be used in production of all plant mix bituminous base, leveling and binder courses. Reclaimed bituminous pavement materials, not to exceed 15 percent of the total mix by weight, may be used in production of all plant mix bituminous surface courses. All reclaimed bituminous pavement materials shall be processed to pass a 2-inch sieve.